



INSTRUCTIONS:

Congratulations! You have purchased **Surf Splash**, the BEST device ever invented for washing sand and debris from the feet and lower legs and the ONLY automatic foot shower on the market. For assembly and installation, please follow the diagram and instructions in this pamphlet. A Troubleshooting Guide is included.

The following items are included:

- Surf Splash unit
- Side panels (2)
- Carriage bolts & nylon acorn nuts for side panels (4 each)
- Garden hose adapter & rubber washer (1)
- Short pipe, threaded on each end (1)

After assembly and installation, test the unit by stepping onto the center of the platform. It may take a few seconds for the water spray to fully develop. Step off the platform to stop the water spray. ***There will be a small amount of water dribble from the lowest nozzles for approximately 30 - 60 seconds. This is normal drain down.***

Tips for Best Performance:

1. Choose a location for placement of the unit that is relatively flat and level.
2. Make sure that the water supply line has proper pressure. Surf Splash works best when connected to a water system with 45-60 psi. Most public water systems are regulated within this range. Refer to the Trouble Shooting Guide if you think your water pressure may be above or below 45-60 psi.
3. Replace the spray nozzles, cam roller bushings, red bushings and springs annually.
4. Periodically, clean sand from underneath the unit by spraying water under the unit or by moving the unit and sweeping. If the unit is placed upon a raised deck, it is recommended that the unit be mounted upon a fiberglass grate, if possible, to permit sand to fall beneath the deck, OR simply cut a 12" x 12" square hole under the center of the unit (but insure that the unit remains well supported).

If you experience a problem with
your Surf Splash, DO NOT hesitate to contact us.
(866)745-SURF or email at: support@surfsplash.com

Thank you! Your complete satisfaction is our #1 goal!